

Product Highlights

High Performance

- 7060XE7-64PS: 64x OSFP-IHS 1600G ports
- 7060XE7-64PRS: 64x OSFP-RHS 1600G ports
- 7060XE7-64PRS-RV3-L: 64x OSFP-RHS 1600G ports, liquid cooled, ORv3 rack
- 7060XE7-128PE: 128x OSFP 800G ports
- 102.4 Tbps Bandwidth

Cloud Optimized Design

- Fully liquid-cooled option available
- 8 lanes of 200G per 1600G OSFP-IHS or OSFP-RHS port
- Additional 1x 100G QSFP28 front panel port
- Compact form factors with high density
- Compatible with standard 19" and, Open Rack Version 3 (ORv3)
- AC and DC power options
- Removable Supervisor complex
- High-speed field-replaceable fans, front-to-back cooling (in the air-cooled switches)
- Field-replaceable PSUs
- 1x Console port
- 2x RJ45 Ethernet management ports
- 1x USB port

AI/ML ready

- Cluster Load Balancing (CLB)
- Dynamic Load Balancing (DLB)
- Congestion Signaling (CSIG)
- Fast CNP*
- Advanced DCQCN
- RoCEv2
- PFC/ECN for ensuring congestion-free and lossless deployments
- PFC-aware DLB
- PFC-aware ECN
- Workload and NIC integration
- Packet Spraying
- Packet Trimming

Overview

As AI clusters evolve, the network connectivity required for connecting the XPU's together has also evolved. As different architectures like scale-up, scale-out and scale-across become commonly deployed, the network fabric required for interconnectivity is more important than ever before. The bandwidth, speeds and feeds, and software enhancements required to ensure a lossless and congestion-free network are some of the primary factors that are driving the adoption of the next generation AI networks.

Architectures optimized for flexibility are now giving way to systems optimized for performance at scale. The Arista 7060XE7 portfolio of switches represents this next step in the evolution of the networking infrastructure.

Delivering 102.4 Tbps of bandwidth per system, the Arista 7060XE7 series offers high density and wide radix in compact form factors, that serve as the essential building blocks for the most demanding next generation network architectures.



Arista 7060XE7 Series: 7060XE7-64PS and 7060XE7-64PRS



Arista 7060XE7 Series: 7060XE7-64PRS-RV3-L



Arista 7060XE7 Series: 7060XE7-128PE

Model Overview

The **7060XE7-64PS** and **7060XE7-64PRS** deliver the highest performance of 102.4 Tbps, combined with a rich suite of software features, making them ideal for deployments in large scale AI networks. These systems address the crucial challenges of increasing network capacity and efficiency through lower power consumption, enhanced automation and advances in scalability.

The 7060XE7-64PS has 64 ports of 1600G in the OSFP-IHS form factor, while the 7060XE7-64PRS has 64 ports of 1600G in the OSFP-RHS form factor, with both the options providing high density 1600G capabilities in a compact 4RU footprint. The system is designed to support a wide ecosystem of high-speed, high-power interconnectivity options.

Each of these ports can be further broken out into 800GbE, 400GbE and 200GbE to build the most flexible and scalable networks, and support a wide variety of LPO, LRO, 2FR4 and 2DR4 optics.

These 7060XE7-64PS and 7060XE7-64PRS have field-removable and field-replaceable fans and power supplies, to ensure redundancy and optimal performance even under the most demanding load conditions.

These systems can be deployed in standard 19" deployments, as well as ORv3 deployments.

For the 19" deployments, both AC and DC PSU options are available.

The 7060XE7-64PS and 7060XE7-64PRS also have a field-removable and field-replaceable Supervisor complex, that allows for utmost resiliency, while also improving the flexibility, reliability and device uptime.



Front view of the Arista 7060XE7-64PS and 7060XE7-64PRS



Rear view of the Arista 7060XE7-64PS and 7060XE7-64PRS

The **7060XE7-64PRS-RV3-L** is Arista's first purpose-built fully liquid-cooled switch, that delivers the highest performance of 102.4 Tbps, in a compact 20U form factor.

The system provides high density 1600G capabilities in the OSFP-RHS form factor, and is designed to support a wide ecosystem of high-speed, high-power interconnectivity options.

Each of these ports can be further broken out into 800GbE, 400GbE and 200GbE to build the most flexible and scalable networks, and support a wide variety of LRO, 2FR4 and 2DR4 optics.

These 7060XE7-64PRS-RV3-L also has a field-removable and field-replaceable Supervisor complex, that allows for utmost resiliency, while also improving the flexibility, reliability and device uptime.

The 7060XE7-64PRS-RV3-L can be used in standalone single-switch configurations, or in pre-configured canisters with liquid-cooling support, that can fit into integrated racks.

The liquid-cooling manifolds are adaptable to a variety of quick disconnect (QD) standards, including UQD0X and BMQC. Arista's liquid-cooled switches are designed to support both these QD standards, enabling tight integration across diverse rack- and cooling-architectures.



Front view of the Arista 7060XE7-64PRS-RV3-L



Rear view of the Arista 7060XE7-64PRS-RV3-L

The illustration below depicts the exploded view of an integrated rack. The liquid-cooled networking switches, liquid-cooling manifolds, power components can all be integrated within a rack, to work as a highly-scalable and flexible solution.



Exploded view illustration of a fully-integrated rack

The **7060XE7-128PE** has 128 OSFP-IHS ports of 800GbE, in a compact 4RU footprint. Designed to be fully backward compatible with existing 800GbE infrastructure, the 7060XE7-128PE provides an unprecedented 102.4 Tbps of bandwidth.

The ports can be further split into 400GbE, 200GbE or 100GbE to provide high radix.



Front view of the Arista 7060XE7-128PE



Rear view of the Arista 7060XE7-128PE

The 7060XE7-128PE has field-removable and field-replaceable fans and power supplies, to ensure redundancy and optimal performance even under the most demanding load conditions.

These systems can be deployed in standard 19" deployments, as well as ORv3 deployments.

For the 19" deployments, both AC and DC PSU options are available.

Operating System

The Arista 7060XE7 series runs the same Arista EOS software as all Arista products, simplifying network administration, orchestration, and ease of deployment. Arista EOS is a modular switch operating system with a unique state sharing architecture that cleanly separates switch state from protocol processing and application logic. Built on top of a standard Linux kernel, all EOS processes run in their own protected memory space and exchange state through an in-memory database. This multi-process state sharing architecture provides the foundation for in-service-software updates and self-healing resiliency.

In addition to Arista EOS, these platforms also support open source operating systems while leveraging Arista blue box capabilities such as Arista Netdi or Network Diagnostics Infrastructure.

AI Analyzer

AI/ML traffic patterns exhibit unique ramp up behavior in very short intervals of time. Traditional software-based traffic counters do not lend themselves to examine these unique flows. The AI Analyzer is an integrated hardware capability that enables the collection of ECMP member utilization data, aggregated over extremely short periods of time, as granular as 100 microseconds. This allows the Arista 7060XE7 series to effectively analyze these traffic patterns. The results can then be applied to fine tune dynamic load balancing workloads uniformly across the member links, to optimize AI/ML applications.

Dynamic Load Balancing (DLB)

Traditional hash-based load balancing algorithms can result in link and path allocations with short term imbalances and under utilization of aggregate capacity. This is aggravated further in modern data centers with high traffic loads, varied flow duration, mixed packet sizes and micro-bursts. DLB enhancements to load balancing consider the real time load on links and dynamically assign new and existing flows to the best link. When imbalances are detected, active flows and new flows are allocated to the least loaded paths to reduce the possibility of drops. Supported with any combination of ECMP and LAG/MLAG, DLB delivers higher throughput with enhanced load distribution while offering the user an open implementation. An efficient load balancing implementation helps in avoiding bottleneck in AI networks, resulting in efficient utilization of the job completion cycles.

Cluster Load Balancing (CLB)

Cluster Load Balancing (CLB) is an innovative new AI load balancing mechanism, that utilizes RDMA queue pairs to ensure optimal link utilization. AI clusters typically have low quantities of large bandwidth flows, which can result in high tail end latency. CLB solves that problem by doing RDMA-aware flow placement to ensure high performance for all flows with low tail latency.

Load balancing methods that perform local load-aware flow placement maximize the leaf-to-spine link utilization. However, such locally optimized methods fail on the reverse path - there is typically no ability to perform load balancing on the spine-to-leaf path as every spine often only has one path to the destination leaf. CLB approaches this problem with a global view, and is able to simultaneously optimize both the leaf-to-spine and spine-to-leaf flows.

Enhanced Congestion Control

DCQCN, ECN, and PFC are mechanisms used in data center networks to manage congestion. DCQCN uses a quantized congestion notification algorithm, ECN uses a CE bit to signal network congestion, and PFC uses priority-based flow control to signal network congestion. These mechanisms work collectively to help improve network performance by reducing the probability of packet loss, ensuring that data center networks handle the demands of modern workloads. Within ECN, the addition of enhancements including latency-based marking, throughput-based marking, and dynamic marking provide intelligent controls for scalable congestion control.

Maximum Flexibility for Scale Out Network Designs

- Wide choice of optics and cables for multi-speed flexibility from 100G to 1600G
- Support for Linear Pluggable Optics (LPO's) that result in significantly lower power consumption and tremendous cost savings
- 256-way ECMP for scalable designs and to balance traffic evenly across large scale multi-tier designs
- Advanced feature set including Enhanced ECMP Hashing and DLB consider real-time loads and dynamically assign new and existing flows to improve performance
- Advanced Multipathing improves congestion management by rebalancing flows in large scale environments
- Hitless speed changes from 1600G to 100G eliminate down-time when implementing speed changes
- Intelligent congestion control mechanisms including PFC, ECN and QoS deliver advanced tuning to prevent network bottlenecks

Precise Data Analysis

Arista's Streaming Telemetry, Latency Analyzer (LANZ), and AI Analyzer are integrated features of EOS. Together these capabilities provide a complete solution to the monitoring and visibility challenges at speeds up to 1600Gbps giving IT operations the ability to proactively deliver feedback on congestion events, filter, replicate, aggregate and capture traffic without affecting production performance. EOS monitoring features include both event triggered monitoring for real-time micro-burst and congestion tracking as well as high rate counter polling down to 1ms granularity.

Virtualization

Supporting next-generation virtualized data centers and AI/ML networks requires tight integration with orchestration tools and encapsulation technologies such as VXLAN. The 7060XE7 builds on the valuable tools already provided by the Arista VM Tracer suite to integrate directly into encapsulated environments. Offering a wire-speed gateway between VXLAN and traditional L2/3 environments, they make integration of non-VXLAN aware devices including servers, firewalls and load-balancers seamless and provide the ability to leverage VXLAN as a standards based L2 extension technology for non-MPLS environments.

CloudVision® for Accelerated Computing

CloudVision is a network-wide approach for workload orchestration and workflow automation as a turnkey solution for Accelerated Computing. CloudVision extends the EOS publish-subscribe architectural approach across the network for state, topology, monitoring and visibility.

CloudVision combined with Arista Validated Designs (AVD) enables a template driven automated common configuration model to be deployed deterministically across all network elements, implementing best-practice configuration parameters with minimal user input. When combined with the Arista AI Agent for compute hosts, configuration consistency and visibility is extended into the compute platform improving cluster deployment time, operational stability and end to end telemetry.

EOS Licensing

Arista 7060XE7 Series with EOS and CloudVision, is designed to provide flexibility both in the choice of the appropriate feature functionality and in the software consumption model. The base feature set of Arista EOS comes bundled with the Arista products and systems. A set of feature licenses are available to enable additional functionality in advanced feature sets. The traditional licensing procurement model employs a perpetual term for the right to use the feature, set at a fixed price. For Arista CloudVision the functionality is available as a monthly subscription, for an agreed upon term.

Supported Features in EOS

For the latest feature support on these platforms, please visit

<https://www.arista.com/en/support/product-documentation/supported-features>

Layer 2 Features

- 802.1w Rapid Spanning Tree
- 802.1s Multiple Spanning Tree Protocol
- Rapid Per VLAN Spanning Tree (RPVST+)
- 4096 VLANs
- 802.3ad Link Aggregation/LACP
 - 64 ports/channel
 - 128 groups per system
- Multi-Chassis Link Aggregation (MLAG)
 - 64 ports per MLAG
- Custom LAG Hashing
- Resilient LAG Hashing
- 802.1AB Link Layer Discovery Protocol
- Jumbo Frames (9216 Bytes)
- IGMP v1/v2/v3 snooping
- Storm Control

Layer 3 Features

- Routing Protocols: OSPF, OSPFv3, BGP, MP-BGP, IS-IS, and RIPv2
- 256-way Equal Cost Multipath Routing (ECMP)
- Resilient ECMP Routes
- VRF
- BFD
- Route Maps
- IGMP v2/v3
- PIM-SM / PIM-SSM
- Anycast RP (RFC 4610)
- VRRP
- Virtual ARP (VARP)
- Policy Based Routing (PBR)

Advanced Monitoring and Provisioning

- Zero Touch Provisioning (ZTP)
- AI Analyzer*
- Traffic statistics polling at rates as low as 100 msec
- Optional traffic statistics fast polling as low as 1 msec rate
Latency Analyzer and Microburst Detection (LANZ)
 - Configurable Congestion Notification (CLI, Syslog)
 - Streaming Events (GPB Encoded)
 - Capture/Mirror of congested traffic
- Advanced Monitoring and Aggregation
 - Port Mirroring (4 active sessions)
 - L2/3/4 Filtering on Mirror Sessions
 - Mirror to CPU
 - True Egress Mirror

- Advanced Event Management suite (AEM)
 - CLI Scheduler
 - Event Monitor
 - Linux tools
- Integrated packet capture/analysis with TCPDump
- RFC 3176 sFlow

Virtualization Support

- VXLAN Routing and Bridging
- VM Tracer VMware Integration
 - VMware vSphere support
 - VM Auto Discovery
 - VM Adaptive Segmentation

Security Features

- IPv4 / IPv6 Ingress & Egress ACLs using L2, L3, L4 fields
- ACL Drop Logging and ACL Counters
- Control Plane Protection (CPP)
- PDP
- Service ACLs
- DHCP Relay / Snooping
- TACACS+
- RADIUS

Quality of Service (QoS) Features

- Up to 8 Unicast and 2 Multicast queues per port
- DSCP based classification and remarking
- Explicit Congestion Notification (ECN)
- QoS interface trust (COS / DSCP)
- Strict priority queueing
- Weighted Round Robin (WRR) Scheduling
- Per-Priority Flow Control (PFC)
- Data Center Bridging Extensions (DCBX)
- ACL based Policing and DSCP Marking
- Per port MMU Configuration
- Policing/Shaping
- Rate limiting

Advanced Load Balancing Features

- Dynamic Load Balancing (DLB)
- Cluster Load Balancing (CLB)

Network Management

- CloudVision
- 10/100/1000 Management Port
- RS-232 Serial Console Port
- USB Port
- SNMP v1, v2, v3
- Management over IPv6
- Telnet and SSHv2
- Syslog
- AAA
- Industry Standard CLI

Extensibility

- Linux Tools
 - Bash shell access and scripting
 - RPM support
 - Custom kernel modules
- Programmatic access to system state
 - Python
 - C++
- Native KVM/QEMU support

Standards Compliance

- 802.1D Bridging and Spanning Tree
- 802.1p QOS/COS
- 802.1Q VLAN Tagging
- 802.1w Rapid Spanning Tree
- 802.1s Multiple Spanning Tree Protocol
- 802.1AB Link Layer Discovery Protocol
- 802.3ad Link Aggregation with LACP
- 802.3ae 10 Gigabit Ethernet
- 802.3ba 100 Gigabit Ethernet
- 802.3bs 400 and 200 Gigabit Ethernet
- 802.3cm 400 Gigabit over multimode fiber
- RFC 2460 Internet Protocol, Version 6 (IPv6) Specification
- RFC 4861 Neighbor Discovery for IP Version 6 (IPv6)
- RFC 4862 IPv6 Stateless Address Autoconfiguration
- RFC 4443 Internet Control Message Protocol (ICMPv6) for the Internet Protocol Version 6 (IPv6) Specification
- 800GBASE-ETC

SNMP MIBs

- RFC 3635 EtherLike-MIB
- RFC 3418 SNMPv2-MIB
- RFC 2863 IF-MIB
- RFC 2864 IF-INVERTED-STACK-MIB
- RFC 4292 IP-FORWARD-MIB
- RFC 4363 Q-BRIDGE-MIB
- RFC 4188 BRIDGE-MIB
- RFC 2013 UDP-MIB
- RFC 2012 TCP-MIB
- RFC 2011 IP-MIB
- RFC 2790 HOST-RESOURCES-MIB

- RFC 3636 MAU-MIB
- RMON-MIB
- RMON2-MIB
- HC-RMON-MIB
- LLDP-MIB
- LLDP-EXT-DOT1-MIB
- LLDP-EXT-DOT3-MIB
- ENTITY-MIB
- ENTITY-SENSOR-MIB
- ENTITY-STATE-MIB
- ARISTA-ACL-MIB
- ARISTA-QUEUE-MIB
- RFC 4273 BGP4-MIB
- RFC 4750 OSPF-MIB
- ARISTA-CONFIG-MAN-MIB
- ARISTA-REDUNDANCY-MIB
- RFC 2787 VRRPv2-MIB
- MSDP-MIB
- PIM-MIB
- IGMP-MIB
- IPMROUTE-STD-MIB
- SNMP Authentication Failure trap
- ENTITY-SENSOR-MIB support for DOM (Digital Optical Monitoring)
- User configurable custom OIDs

Table Sizes

STP Instances	62 (MST)/62 (RPVST+)
IGMP Groups	128K, with 512 unique groups
ACLs	2304
Egress ACLs	512
ECMP	256-way, 4K groups, 32K members
MAC Addresses	136K
IPv4 Host Routes	500K
IPv4 Multicast (S,G)	256K
IPv4 LPM Routes	1M
IPv6 LPM Routes - Unicast (prefix length <= 64)	600K
IPv6 LPM Routes - Unicast (any prefix length)	600K

See EOS release notes for latest supported MIBs

* Not currently supported in EOS

Model Comparison	7060XE7-64PS	7060XE7-64PRS	7060XE7-64PRS-RV3-L	7060XE7-128PE
Ports	64x 1600G OSFP-IHS 1x 100G QSFP28	64x 1600G OSFP-RHS 1x 100G QSFP28	64x 1600G OSFP-RHS 1x 100G QSFP28	128x 800G OSFP-IHS 1x 100G QSFP28
Throughput (FDX)	102.4 (204.8) Tbps	102.4 (204.8) Tbps	102.4 (204.8) Tbps	102.4 (204.8) Tbps
1600G Ports	64	64	64	-
800G Ports	128	128	128	128
400G Ports	256	256	256	256
200G Ports	512	512	512	512
System Memory	32 Gigabytes	32 Gigabytes	32 Gigabytes	32 Gigabytes
Flash Storage Memory	480 Gigabytes	480 Gigabytes	480 Gigabytes	480 Gigabytes
Packet Buffer Memory	267 MB	267 MB	267 MB	267 MB
10/100/1000 Mgmt Ports	2	2	2	2
RS-232 Serial Ports	1 (RJ-45)	1 (RJ-45)	1 (RJ-45)	1 (RJ-45)
USB Ports	1	1	1	1
Hot-swappable Fans (Dual rotor)	8	8	-	8
Airflow Direction	Front to Rear	Front to Rear	-	Front to Rear
Fan Tray	FAN-7310H-RED	FAN-7310H-RED	-	FAN-7310H-RED
Power	PWR-3211-HV-RED	PWR-3211-HV-RED	-	PWR-2411-HV-RED
Typical Power Draw*	TBD	TBD	TBD	TBD
Max Power Draw*	TBD	TBD	TBD	TBD
Dimensions (WxHxD)	440 mm x 174 mm x 581.5mm	440 mm x 174 mm x 581.5mm	537 mm x 94.5 mm x 805 mm	440 mm x 176 mm x 755 mm
Weight	86 lbs (39 kg)	86 lbs (39 kg)	100 lbs (45 kg)	93 lbs (42 kg)

Power Supply	PWR-2421 HV	PWR-2411-MC-RED	PWR-2411-DC-RED	PWR-3211-HV-RED
Input Voltage	200-277 VAC 240-380 VDC	48-60 VDC	40-72V DC	200-277 VAC, 240-380 VDC
Typical Input Current	13.5A at 200V AC	60 - 50 A Max (48 - 60 V)	42A at -48V	18A at 200VAC
Input Frequency	50/60Hz AC or DC	DC	DC	50/60Hz AC or DC
Output Power	2400W	2400W	2400W	3200W
Input Connector	SAF-D	6-Pin M-CRPS	AWG #2-4 Dual-hole Lugs	SAF-D
Efficiency (Typical)	96%	96%	94%	96%

Arista Optics and Cables

The Arista 7060XE7 Series supports a wide range of 100G to 1600G pluggable optics and cables. For details about the different optical modules and the minimum EOS Software release required for each of the supported optical modules, visit <https://www.arista.com/en/products/transceivers-cables>

Standards Compliance

EMC	FCC A ICES-003 Issue 7 EN 55032:2015 EN IEC 61000-3-2:2019 EN 61000-3-3 KS C 9832 VCCI-CISPR 32:2016 AS/NZS CISPR 32:2015 +A1 2020 EN 300 386, TEC/SD/DD/EMC-221 CNS 15936 BS EN 55032:2015+A11:2020 BS EN IEC 61000-3-2 BS EN 61000-3-3
Immunity	EN 55035:2017+A11:2020 EN 300 386 KS C9835 BS EN 55035:2017+A11:2020
Safety	EN 62368-1:2020+A11:2020 EN 62368-1:2014+A11:2017 IEC 62368-1: 2018 Korea KC Safety KC 62368-1 (2021-08) CSA/UL 62368-1:2019 NOM 019-SCFI-1998 CNS 15598-1 AS/NZS 62368.1:2022
Certifications	BSMI (Taiwan) FCC Class A (United States) ICES-003 (Canada) CE (European Union) KCC (South Korea) NRTL (North America) RCM (Australia / New Zealand) UKCA (United Kingdom) VCCI (Japan) TEC (India) ANATEL (Brazil) ICASA (South Africa) NOM Equivalency (Mexico)
European Union Directives	2014/35/EU Low Voltage Directive 2014/30/EU EMC Directive 2012/19/EU WEEE Directive 2011/65/EU RoHS Directive 2015/863/EU Commission Delegated Directive
Further Information	Product Certification Portal

Environmental Characteristics

Operating Temperature ¹	0 to 40°C (32 to 104°F)
Storage Temperature	-40 to 70°C (-40 to 158°F)
Relative Humidity	5 to 90%
Operating Altitude	0 to 10,000 ft, (0-3,000m)

1. Certain airflow configurations or the use of higher power or reduced temperature range optics may reduce maximum operating temperature or operating altitude.

Ordering SKU	Product Description
DCS-7060XE7-64PS-F	Arista 7060XE7, 64 x 1600GbE OSFP front panel ports, front-to-rear air, 4xAC
DCS-7060XE7-64PS#	Arista 7060XE7, 64 x 1600GbE OSFP front panel ports, front-to-rear air, no fans, no psu
DCS-7060XE7-64PRS-F	Arista 7060XE7, 64 x 1600GbE OSFP-RHS front panel ports, front-to-rear air, 4xAC
DCS-7060XE7-64PRS#	Arista 7060XE7, 64 x 1600GbE OSFP-RHS front panel ports, front-to-rear air, no fans, no psu
DCS-7060XE7-64PRS-RV3-L	Arista 7060XE7, 64 x 1600GbE OSFP-RHS front panel ports, liquid cooled, ORv3
DCS-7060XE7-128PE-F	Arista 7060XE7, 128 x 800GbE OSFP front panel ports, front-to-rear air, 4xAC
DCS-7060XE7-128PE#	Arista 7060XE7, 128 x 800GbE OSFP front panel ports, no fans, no psu

Spares	Product Description
FAN-7310H-RED	Spare high speed fan module for Arista 7000 series switches (front-to-rear airflow)
PWR-3211-HV-RED	Spare PSU, 1RU, HVAC/HVDC, 3200W, FORWARD, 73.5MM
PWR-2421-HV-RED	Arista 2400W HV AC and DC Power Supply, FORWARD, 73.5MM
PWR-2411-MC-RED	Arista PSU, 1RU, +48VDC, 2400W, 6-PIN Modular Connector, FORWARD, 73.5MM
PWR-2411-DC-RED	Arista 2400W DC Power Supply, FORWARD, 73.5MM
DCS-7004-SUP-L	7004 series Supervisor-L module with 8c/16t, 32GB RAM, 480GB NVMe (spare)

Warranty

The Arista 7060XE7 switches comes with a one-year limited hardware warranty, which covers parts, repair, or replacement with a 10 business day turn-around after the unit is received.

Service and Support

Support services including next business day and 4-hour advance hardware replacement are available. For service depot locations, please see: <http://www.arista.com/en/service>

Headquarters

5453 Great America Parkway
Santa Clara, California 95054
408-547-5500

Support

support@arista.com
408-547-5502
866-476-0000

Sales

sales@arista.com
408-547-5501
866-497-0000

www.arista.com

ARISTA