

Model Number	C-360	W-318	C-250/C-260	C-230/C-230E	O-235/O-235E	C-200
Description	Indoor tri-band AP for highest deterministic performance (voice, video, data), ultra-high density. Persistent RF analysis by dedicated multifunction radio.	Indoor tri-band wall plate AP or desktop stand, optimized for medium density environments with Ethernet/PoE ports to connect wired devices.	Indoor AP for highest deterministic performance (voice, video, data), ultra-high density. Persistent RF analysis by multi-function third radio	Indoor AP for high deterministic performance (voice, video, data), high density. Persistent RF analysis by multi-function third radio	Outdoor AP for high deterministic performance (voice, video, data), high density. Persistent RF analysis by multi-function third radio	Indoor AP for low/medium density deployments
Radio Components	802.11b/g/n/ax radio (2.4 GHz)	802.11b/g/n/ax radio (2.4 GHz)	802.11b/g/n/ax radio (2.4 GHz)	802.11b/g/n/ax radio (2.4 GHz)	802.11b/g/n/ax radio (2.4 GHz)	802.11b/g/n/ax radio (2.4 GHz)
	802.11a/n/ac/ax radio (5 GHz)	802.11a/n/ac/ax radio (5 GHz)	802.11a/n/ac/ax radio (5 GHz)	802.11a/n/ac/ax radio (5 GHz)	802.11a/n/ac/ax radio (5 GHz)	802.11a/n/ac/ax radio (5GHz)
	802.11ax radio (6 GHz)	802.11ax radio (6 GHz)				
	802.11a/b/g/n/ac/ax multifunction radio		s802.11a/b/g/n/ac multifunction radio	802.11a/b/g/n/ac multifunction radio	802.11a/b/g/n/ac multifunction radio	
	BLE/ZigBee	BLE/ZigBee	BLE	BLE	BLE	
	Internal antenna	Internal antenna	Internal antenna	Internal/External antenna	Internal/External antenna	Internal antenna
Ports	2 x 10Gb Ethernet	1 x 2.5Gb Ethernet + 3x 1Gb Ethernet	2 x 5Gb Ethernet	1 x 5Gb Ethernet + 1 x Gb Ethernet	1 x 5Gb Ethernet + 1 x Gb Ethernet	1 x Gb Ethernet
	Console	Console	Console	Console		Console
	USB3.0	USB	USB	USB	USB	
Max Data Rate	4.8 /4.8/1.2 Gbps	2.4 /1.2/0.574 Gbps	4.8 / 1.2 Gbps	2.4 Gbps / 574 Mbps	2.4 Gbps / 574 Mbps	1.2 Gbps / 574 Mbps
Spatial Streams	4x4 (2.4GHz); 4x4 (5GHz); 4x4 (6GHz)	2x2 (2.4GHz); 2x2 (5GHz); 2x2 (6GHz)	8x8:8 (5GHz) / 4x4 (2.4GHz)	4x4:4 (5GHz) / 2x2 (2.4GHz)	4x4:4 (5GHz) / 2x2 (2.4GHz)	2x2:2 (5GHz) / 2x2:2 (2.4GHz)
Channel Width	20/40/80/80+80/160 MHz	20/40/80/80+80/160 MHz	20/40/80/80+80/160 MHz	20/40/80/160 MHz	20/40/80/160 MHz	20/40/80 MHz
Power	802.3bt 802.3at (reduced functionality)	802.3bt 802.3at (reduced functionality)	802.3bt 802.3at (3dB power reduction)	802.3at 802.3af (reduced functionality)	802.3at 802.3af (reduced functionality)	802.3af
	DC power	DC power	DC power	DC Power		DC Power
Dedicated WIPS	No	No	Yes	Yes	Yes	Yes
Mesh	Yes	Yes	Yes	Yes	Yes	Yes
LTE Interference Mitigation	Yes	Yes	Yes	Yes	Yes	Yes
Wi-Fi Alliance Certification	In process	Pending	Yes	Yes	Yes	Yes
SKU	AP-C360	AP-W318	AP-C260	AP-C230, AP-C230E	AP-O235, AP-O235E	AP-C200

For complete country certification records, please visit the [product certificate page](#) on Arista website.

For Antenna selection for models with external antenna connectors, please see the [Antenna Selection Guide](#).

All Arista Wi-Fi Access Points support WIPS functionality, either via the multi-function radio or with background scan enabled on the access radios.